



New SX400

-Middle Range Multi-Purpose Camera-

Featuring a 32x optical zoom lens

Covers a wide range of focal lengths from 12.5mm wide-angle to 400mm telephoto (horizontal angle of view: 31.8°~1.0°), accommodating diverse needs.

Compact and lightweight body

Approximately 30% smaller and over 40% lighter than previous models. Ideal for vehicle mounting and portable applications.

Features a newly developed F2.8 lens

Provides clear, low-noise images even in low-light conditions such as at night or in bad weather.

Specification

Optical zoom	32x
Digital zoom	1.25x, 1.5x, 1.75x, 2x
Effective sensor size	1/1.8"
Focal length	12.5mm~400mm
Maximum aperture ratio	F2.8 (12.5mm) – F5.2 (400mm)
Angle of view [16:9 (H x V)]	12.5mm 31.8° x 18.4° 400mm 1.00° x 0.57°
Focus settings	Continuous AF, Quick AF, Manual
Iris	Auto, Manual (Aperture range : F2.8 – F16)
Shutter speed	Auto (with minimum speed selection of 1/8 – 1/125s), Manual (1 – 1/32000s)
Image stabilization	Auto (OIS+EIS), OIS, EIS, OFF
Heat haze reduction	Selectable (3 levels)
Fog reduction	Selectable (3 levels)
Video output systems	HDMI, HD-SDI, Composite(BNC)
External interfaces	Ethernet (10Base-T, 100Base-TX, RJ45 connector), RS-485, External trigger (Day / Night)
RS-485 compatible protocol	Pelco-D / Pelco-P (including extended commands)
Network protocols	ICMP, ARP, TCP/IP, UDP/IP, HTTP, RTSP, RTP, DHCP, DNS, RTP/RTCP, SNTP
ONVIF support	Yes (Profile S)
Size (H x W x L)	Approx. 120mm x 134mm x 302mm
Weight	Approx. 3.9kg



Warning

For Your Safety

Be certain to read the instruction for use before using any equipment.

*Product specifications, appearance, price, etc. are subject to change without advance notice.

*Product colors in this catalog may differ in appearance from the actual product due to photography and printing conditions.

